



# HIGH PERFORMANCE Dry Chemical

**Manufactured and Tested to  
ANSI/UL Standards**

**Amerex is an ISO-9001:2000  
Registered Firm**

## EXTRA FEATURES:

- ★ Superior Range (Vertical & Horizontal)
  - ★ High (240 PSI) Operating Pressure
  - ★ Choice of Chemicals
    - ABC Multi Purpose, Regular, Purple K
  - ★ Select *Fast Flow* for:
    - High Flow Rate
    - Fast Discharge
    - Quicker Knockdown
    - More Operator Protection
  - ★ Select Compliance Flow for:
    - Long Range
    - Highest U.L. Ratings
  - ★ Epoxy Painted GALVANIZED STEEL Cylinders  
(The best corrosion protection available anywhere)
  - ★ Protective Rubber Foot Rings
  - ★ All Metal Valve Construction
  - ★ Gauge Guards
  - ★ Bar Coded Labels
- (Temperature Range -65°F to 120°F)**

**Note: All extinguishers are U.S. Coast Guard  
approved with bracket listed on U.L. label**

## Stored Pressure



**HIGH PERFORMANCE** extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use and extreme environment applications. Economical - less initial cost, lower maintenance costs and greater reliability than cartridge operated extinguishers.

Available in 250 lb. Wheeled and Stationary extinguishers.

## 12 YEAR WARRANTY

SPECIFICATIONS	HIGH PERFORMANCE - ABC, REGULAR, PURPLE K Dry Chemical														
Type	FAST FLOW									COMPLIANCE FLOW					
Agent	ABC			REGULAR			PURPLE K			ABC			PURPLE K		
Size & Capacity - lbs. (kg)	13.2 (6)	20 (9)	30 (13.6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)
Model Number	594	581	567	582	568	595	580	584	569	592	564	589	599	566	591
U/L Rating	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	20A:120B:C	20A:160B:C	80B:C	120B:C	160B:C
Shipping Wt. (lbs.)	31	42½	58	42½	58	31	42½	42½	58	31	42½	58	31	42½	58
Height (in.)	17½	24¾	26½	24¾	26½	17½	24¾	24¾	26½	17½	24¾	26½	17½	24¾	26½
Width (in.)	10½	10½	11	10½	11	10½	10½	10½	11	10½	10½	11	10½	10½	11
Depth (Diam. - in.)	7	7	8	7	8	7	7	7	8	7	7	8	7	7	8
Range (ft.)	40-50			40-50			40-50			40-50			40-50		
Discharge Rate (Ave.) (lbs./sec.)	.94	1.20	1.60	1.40	1.76	.94	1.44	2.00	1.88	.59	.65	.95	.61	.67	.81
Discharge Time (sec.)	15	18	21	15	17	15	15	10	16	22	30	34	22	29	34
Standard Bracket	Wall														