

## CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHERS



- **Carbon Dioxide**, a gaseous agent for class B and C fires.
- **Ideal Uses:** chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, airport ramps, boat docks and large laboratories.
- Manufactured to ANSI/UL 154 and ANSI/UL 711 standards.

| <b>SPECIFICATIONS</b>    | <b>PORTABLE UNITS</b>                 |  |                                       |                                       |
|--------------------------|---------------------------------------|--|---------------------------------------|---------------------------------------|
| SIZE/MODEL               | 5CD                                   | 10CD                                   | 15CD                                  | 20CD                                  |
| PART NO. ALUM. VALVE     | 45100                                 | 45600                                  | 46100                                 | 46600                                 |
| VALVE                    | CHROME PLATED BRASS                   |  |                                       |                                       |
| CAPACITY lbs./kg)        | 5 • 2.27                              | 10 • 4.54                              | 15 • 6.80                             | 20 • 9.07                             |
| U.L. Rating              | 5B:C                                  | 10B:C                                  | 10B:C                                 | 10B:C                                 |
| Cylinder                 | ALUMINUM                              |  |                                       |                                       |
| Ship wt. (lbs./kg)       | 13 <sup>3</sup> / <sub>4</sub> • 6.3  | 27 <sup>3</sup> / <sub>4</sub> • 12.6  | 37 <sup>3</sup> / <sub>4</sub> • 17.1 | 49 • 22.2                             |
| Height (in./cm)          | 17 <sup>3</sup> / <sub>8</sub> • 44.1 | 19 <sup>3</sup> / <sub>4</sub> • 50.2  | 26 <sup>3</sup> / <sub>8</sub> • 67.0 | 26 <sup>7</sup> / <sub>8</sub> • 68.2 |
| Width (in./cm)           | 8 <sup>1</sup> / <sub>4</sub> • 21.0  | 12 • 30.5                              | 12 • 30.5                             | 13 • 33.0                             |
| Diameter (in./cm)        | 5 <sup>1</sup> / <sub>4</sub> • 13.3  | 6 <sup>15</sup> / <sub>16</sub> • 17.6 | 6 <sup>7</sup> / <sub>8</sub> • 17.5  | 8 • 20.3                              |
| Bracket                  | Wall                                  | Wall                                   | Wall                                  | Wall                                  |
| Range (feet/meters)      | 4-8/1.2-2.4                           | 4-8/1.2-2.4                            | 4-8/1.2-2.4                           | 4-8/1.2-2.4                           |
| Discharge time (seconds) | 8                                     | 10                                     | 15                                    | 20                                    |
| USCG Approved            | Type B:C Size I                       |  | Type B:C Size II                      |                                       |

**PRODUCT DATASHEET LINKS ( PDF )**

|                      |                       |                       |                       |                       |
|----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Part No. Alum. Valve | <a href="#">45100</a> | <a href="#">45600</a> | <a href="#">46100</a> | <a href="#">46600</a> |
|----------------------|-----------------------|-----------------------|-----------------------|-----------------------|