

WET CHEMICAL COOKING APPLIANCE STORED PRESSURE

[\(Download PDF\)](#)

- **WET CHEMICAL** Extinguishers contain a blend of Potassium Acetate and Citrate that is extremely effective in combating fires in today's cooking appliances that use unsaturated cooking oils. This chemical excels in effectively fighting and cooling these very hot and difficult fires. The application of the agent provides a fine mist spray that prevents splashing of the grease and confines it to the cooking surface.
- **Manufactured to ANSI/UL 8 AND ANSI/UL 711 Standards**
Designed to work in conjunction with pre-engineered hood systems. Tested to extinguish one 18" x 24" fat fryer.

SPECIFICATIONS	WET CHEMICAL
100 PSI / 690 kPa	OPERATING PRESSURE
Part Number	50006 (Datasheet)
Application	Hose
Model Number	WC-6 Liter
U.L. Rating	1A:K
Capacity (gal/liters)	1.59 / 6
Shipping Weight (lbs/kg)	22 / 10
Extinguisher Height (in/cm)	19.25 / 48.9
Height w/Hose Installed (in/cm)	25.5 / 64.8
Width w/Hose Installed (in/cm)	11 / 27.9
Cylinder diameter (in/cm)	7 / 17.8
Discharge Time (seconds)	54
Standard Bracket	Wall
Cylinder	Stainless Steel
Temperature range	+40°F to +120°F
USCG Approved	No



**6 LITER WET CHEMICAL FIRE
EXTINGUISHER**